

Product information | TECHNICAL DATA SHEET

TEXTURED BUMPER PAINT

400 ml, 11 Oz, 318 g.

GENERAL DESCRIPTION

Paint formulated with high quality combined nitro resins, with a textured finish especially for bumpers.

FEATURES

- Very fast drying.
- Excelente flexibilidad.
- Easy to apply and recoat.
- Good adhesion.
- Lead free.
- High covering power.

APPLICATIONS

Its use is recommended for the motor industry and especially for painting bumpers.

- Automotive industry.

INSTRUCTIONS FOR USE

- Shake the can vigorously before use, for approximately one minute after hearing the sound of the mixer.
- Apply on clean and dry surfaces.
- About bumper does not need primer.
- Apply thin coats for best results, always thin layers is better than one thick, paintable after 10 minutes with the same paint.
- Disconnect the electrical appliance before painting.
- Use it in well ventilated areas.
- Request safety data sheets.

PHYSICAL PROPERTIES

Binder type:	Combined nitro
Color:	Black, grey
Texture:	Medium
Shine 60°:	Mate
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Total drying (ASTM D-1640 ISO 1517):	20'
Coat thickness (ASTM D-823 ISO 2808):	15 µm/capa (2 applications)
Adherence (ASTM D-3359 ISO 2409):	4B
Theoretical Coverage (continuous painting):	2 m ²
Thinner:	Acetato Butilo
Product life:	(Well Stored) 5 years
Recoating:	After 10'
Painted resistance to heat:	120°C
Application conditions:	T° environment min 8°C T° Surface min 5-50°C
	Humidity max. 85% R.H.P

* Adherence tests were performed on steel.

CAUTION



APPEARANCE



LABEL



EX014PR1041 Black

EX014PR1042 Grey

CAP SYSTEM



Transversal Cap
Fino - Thin

PACKAGING

Nominal capacity 400 ml.
Heat resistance of packaging: <50°C
Propellant: DME
VOC's: 655g/L

Box (6 units)
205 X 140 X 200 mm.

